

DOORS

LIGHT DUTY ROLL-UP



1900 SERIES

The 1900 Series commercial-style roll-up door utilizes 9 1/2" drums instead of 12" drums, which allows it to operate quietly and requires less headroom during installation.

↑ HEADROOM
17" (UP TO 10')
↓ 19" (10'-14')

9 1/2"
DRUM

WARRANTY
30/25
FILM/CHALK-FADE

WeatherXL




NOTE: The 1900 Series is not rated for wind loads. Please see the 2500 Series, 3000 Series, or 5000 Series.

1900 SERIES


LIGHT DUTY ROLL-UP




INTERIOR ELEVATION




GUIDE DETAIL




DOOR ENGAGEMENT




GUIDE MOUNTING



MASONRY MOUNT



STEEL MOUNT



WOOD MOUNT

CURTAIN

- 26-gauge galvanized, Grade E hard steel
- 5/8" ribbed corrugation
- Maximum opening size 12' x 14'
- Siliconized polyester WeatherXL™ paint over prime coat

BOTTOM BAR

- 6063 - T6 aluminum extrusion
- 2" x 1 1/2" galvanized angles
- Bulb astragal
- Stainless steel nuts and bolts

AXLE-DRUM ASSEMBLY

- 15/16" O.D. steel axle, 14-gauge
- 11-gauge axleon doors over 10' wide
- Oil tempered torsion springs
- Utilizes 9 1/2", 18-gauge drums
- Shielded steel ball bearings in drums

A.C.E. (ADVANCED CURTAIN ENGAGEMENT) GUIDE SYSTEM

- Galvanized steel
- Adjustable bolt on head stop
- Polyethylene wear strip
- Pre-punched holes for lock and attachment fasteners

HARDWARE

- 13-gauge saddle clamps
- 10-gauge slide locks, two per door
- 16-gauge step plate; two per door
- 1/4" steel angle T-bracket

OPTIONS

- Chain hoist 4:1 reduction
- Vision panels (17" x 5")
- Hood
- Steel mounting plates
- Available in 24 colors, subject to availability and varying lead times



NOTE: The 1900 Series is not rated for wind loads. Please see the 2500 Series, 3000 Series, or 5000 Series.

JDT Garage Door Service
602-703-9582
info@jdtgaragedoor.com



(800) 542-0501 • info@dbci.com • www.dbci.com