



5000 SERIES

Built to stand up to strong winds caused by tornadoes and hurricanes for years with little-to-no maintenance, the durable 5000 Series door meets the stringent building codes of many coastal areas. Features include deep engagement guides and side curtain "J" shaped windlocks to maintain the operational integrity of the door and comply with most state and local building codes. HEADROOM 20" (UP TO 10') 22" (10'-14') 24" (OVER 14')

EMERGENCY ASSEMBLY POINT










The 5000 Series is wind rated up to 16' wide. The pressure rating increases as the door width decreases.

5000 SERIES

HEAVY DUTY ROLL-UP

INTERIOR ELEVATION





- 26-gauge galvanized, Grade E hard steel
- 5/8″ ribbed corrugation with three-rivet windlock attachment
- Maximum opening size 18' x 16'
- Siliconized polyester WeatherXL[™] paint over prime coat

BOTTOM BAR

- 6063 T6 aluminum extrusion
- 2" x 1¹/₂" galvanized angles
- Bulb astragal
- Stainless steel nuts and bolts

AXLE-DRUM ASSEMBLY

- 15/16″ O.D. steel axle, 14-gauge
- 11-gauge axle on doors over 10' wide
- Utilizes 12″, 16-gauge drums
- Shielded steel ball bearings in drums
- Oil tempered torsion springs

A.C.E. (ADVANCED CURTAIN ENGAGEMENT) GUIDE SYSTEM

- 12-gauge galvanized steel
- 12-gauge wind lock bar
- Adjustable bolt on head stop
- Polyethylene wear strip
- Pre-punched holes for lock and attachment fasteners

HARDWARE

- Saddle clamps with set fasteners
- 10-gauge slide locks, two per door
- 16-gauge step plate; two per door
- ¼" steel angle T-bracket

OPTIONS

- Chain hoist 8:1 reduction
- Header seal
- Hood
- Steel mounting plates
- Motor operated
- Available in 24 colors, subject to availability and varying lead times


JDT Garage Door Service 602-703-9582 info@jdtgaragedoor.com

The 5000 Series is wind rated up to 16' wide. The pressure rating increases as the door width decreases.









STEEL JAMBS RH GUIDE MOUNT SHOWN



02.19



INSIDE