



Aluminum MultiView Doors

Amarr® 3582


Amarr 3582 Aluminum MultiView doors make a unique design statement with the widest single piece of glass that specifications, safety, and reliability standards allow. Constructed of 2" thick extruded aluminum rails and stiles, these doors are built to last. The **ClearView Aluminum Strut System** provides strength and durability without restricting the viewing area. With a wide selection of glass, acrylic and polycarbonate glazing options, in more than two dozen paint and anodize finishes, the Amarr 3582 is a distinctive choice for any building where style and functionality are important.



CONSTRUCTION

Amarr 3582
MultiView Aluminum door

- 2" thick extruded aluminum rails & stiles
- Tongue and groove section joints provide additional protection against the elements
- Equal glass heights in all sections of a door
- Glass expands up to 8'2" wide



Track: All Amarr doors are available with both 2" or 3" track in Standard Lift, High Lift, Vertical Lift, Low Headroom, and Follow the Roof Pitch. Custom track configurations are also available. For drawings and more information, please visit www.amarr.com.

Springs: Torsion springs are oil tempered, helical wound and custom computed for each door for a minimum 10,000 cycle life. Optional springs are available up to 100,000 cycle life.

Hardware: Amarr hardware includes minimum 14-gauge galvanized steel hinges and 13-gauge galvanized steel track brackets. All rollers have minimum 10-ball bearings.

SPECIFICATIONS

	Amarr 3582
MATERIAL	Aluminum
CONSTRUCTION LAYERS	Single
DOOR THICKNESS	2" (5.1cm)
SECTION HEIGHTS ¹	Varies by door height
MINIMUM DOOR WIDTH	2' 0"
MAXIMUM DOOR WIDTH	20' 2" (in 1" increments)
MINIMUM DOOR HEIGHT ¹	6' 0"
MAXIMUM DOOR HEIGHT ¹	20' 1"
CLEARVIEW STRUT SYSTEM	Only required for doors ≥ 16'
WIND LOAD ² AVAILABLE	NA
FINISH WARRANTY ³	5 Years
WORKMANSHIP/HARDWARE WARRANTY ³	1 Year
GLASS WARRANTY ³	1 Year

¹ For complete section and door height configuration charts, visit amarr.com or contact your local Amarr dealer. ² It is your responsibility to make sure your garage door meets local building codes. ³ For complete warranty details, visit amarr.com or contact your local Amarr dealer.

COLORS


Actual color may vary from samples shown.

In Stock Finishes

ANODIZE




PAINT



Special Order Finishes

Longer lead time and price upcharge may apply.

ANODIZE



PAINT - Powder Coat & PVDF

PVDF coating (commonly referred to as Kynar®) is known for its resistance to color fade and corrosion.




RAL and custom paint colors available.
†PVDF only.

GLAZING OPTIONS

	Single Pane										Insulated		
	Tempered				Lami- nated	Polycarbonate			Acrylic			Tempered	
	3/16"	3/16" Low-E	1/4"	1/4" Low-E		Single 1/8"	Single 1/4"	Tri-Wall 5/8"	1/8"	1/4"	1/2"	1/2"	1/2" Low-E
CLEAR	STD	•	•	•		•	•	•	•	•	•	•	•
OBSCURE	•												
GRAY	•											•	•
BRONZE	•							•				•	•
GREEN	•											•	•
FROST	•		•					•				•	
SNOW					•			•					
WHITEOUT					•								
BLACK ICE					•								

DOOR CONFIGURATIONS

For Single Pane Glazing		
Door Width	# Center Stiles	# Windows/Section
Up to 8' 2"	0	2
8' 3" - 16' 2"	1	4
16' 3" - 20' 2"	2	6



For Insulated Glazing		
Door Width	# Center Stiles	# Windows/Section
Up to 10' 2"	1	4
10' 3" - 16' 2"	2	6
16' 3" - 20' 2"	3	8

